



OEM Reader LF

OEM Reader LF Read-only

OEM Reader Stick LF Multitag

OEM Mini Reader LF

OEM Reader LF



Specifications

Supported Tags	read-only, e.g. EM 4100	EM 4102, EM 4550 NXP Hitag 1, 2, S Temic (Option)	EM 4102, EM 4550 NXP Hitag 1, 2, S Temic (Option)	EM 4102, EM 4550 NXP Hitag 1, 2, S Temic (Option)
Dimensions	∅ 26 × 8.5 mm	79 × 27 × 8 mm	30.5 × 25.5 × 9.5 mm	70 × 47.5 × 18 mm
Antenna	Internal	Internal	External	Internal
Temperature Range	-40 ... +85 °C	-20 ... +70 °C	-20 ... +70 °C	-20 ... +70 °C
Power Supply	5VDC	5VDC via USB	5 or 12VDC	5VDC via USB
Read/Write Distance	Up to 10 cm	Up to 5 cm	Up to 10 cm	Up to 7 cm
Interface Options	TTL, Wiegand	TTL, USB	TTL, RS232, RS485	USB, RS232

Order Codes

	R-MOD-ECO125	R-OEM-125-STICK	R-MOD-125	R-OEM-125-USB
			R-MOD-125-232	R-OEM-125-232
			R-MOD-125-485	