


OEM Reader UHF



	OEM Reader Stick UHF	OEM Reader UHF Multitag	OEM Reader MR-UHF	OEM Reader LR-UHF
--	----------------------	-------------------------	-------------------	-------------------



Specifications

ISO 18000-6B C incl.C1G2	- <input checked="" type="checkbox"/>	- <input checked="" type="checkbox"/>	- <input checked="" type="checkbox"/>	- <input checked="" type="checkbox"/>
Dimensions	80 × 21 × 12 mm	40 × 21 × 6 mm	50 × 50 × 8 mm	50 × 50 × 8 mm
Antenna	Internal	External	External	External
Temperature Range	-10 ...+60 °C	-10 ...+60 °C	-10 ...+70 °C	-10 ...+70 °C
Power Supply	5 VDC via USB	5.3 VDC	5 VDC	5 VDC
Signal Output	-	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Transmit Power	0.1 W/+20 dBm (SW adjust.)	0.1 W/+20 dBm (SW adjust.)	0.5 W/+27 dBm (SW adjust.)	1.5 W/+32 dBm (SW adjust.)
Read/Write Distance	Up to 15 cm	Up to 50 cm	Up to 300 cm	Up to 500 cm
Interface Options	USB	TTL, USB	TTL, USB	TTL, USB

Order Codes

R-OEM-UHF-STICK-01W-USB	R-OEM-UHF-01W-TTL	R-OEM-UHF-05W-TTL	R-OEM-UHF-15W-TTL
	R-OEM-UHF-01W-USB	R-OEM-UHF-05W-USB	R-OEM-UHF-15W-USB