



## HF Industrial Reader Advant SR 2CH

### Applications

- Industrial Automation
- Asset Tracking
- Laundry Management
- Access Control

### Features

- HF (ISO 14443A, ISO 15693, ISO 18000-3)
- Solutions for Near Field, Short- & Mid-Range applications
- Possibility of using different RFID Standards parallel in one Application
- Read Modes: Buffered Read Mode, Scan Mode and Notification Mode
- Integrated I/O Ports
- Diagnostic Mode via USB
- Multiple Interface Options
- Ruggedized Product Design and Enclosure
- Common SDK for all BLUEBOX Products
- BLUEBOX SHOW Applications Software
- Real Time Clock

### Description

BLUEBOX HF Advant SR 2CH is a read/write device with two antenna ports. This powerful device can achieve a reading distance up to 15 cm. Advant SR allows Near-Field and Short-Range applications. Both external antennas can be detected separately and work independently. Therefore it is the perfect device, where several readings points are required.

The combination of a modern RFID module with 2 antenna ports and an up-to-date engine enables a fast data processing and high reading rates in one device. A powerful SDK allows for fast development of extensive applications.

## Technical Data

### Mechanical Specifications

Housing-Material	Aluminium
Dimensions	110 x 140 x 60 mm
Weight	ca. 430 g
Protection Class	IP65

### Electrical Specifications

Power Supply	24 VDC $\pm$ 10 %
Power Consumption	3.5 W
Operating Frequency	13.56 MHz
Operating Distance	up to 15 cm
Memory Extension	Micro SD-Slot
Connectors	M12
Digital I/O	2 (opto-isolated)
Antenna Connector	2x Lumberg
Interfaces	Ethernet, RS232, RS485, Profibus

### Features

Status Display	4/8 LEDs
Working Modes	Scan Mode, Notification Mode, Buffered Read Mode, Stand-alone Mode
Integrated Webserver	Remote Configuration & Standalone Mode
Temperature Sensor	On-board
Service Interface	USB

### Environmental Conditions

Operating Temperature	-20°C to +65 °C
Humidity	5% to 95%

### Supported Standards / Tags

ISO 14443A/B, ISO 15693, ISO 18000-3, NXP MIFARE family

### Applicable Standards

EMC	EN 301 489-3
Radio Regulation	EN 302 208-2
Safety	CEI EN 60950-1, CEI EN 50364

### SDK Information

Supported OS	Windows 7, 8
Supported Languages	C#, C++, serial command protocol

\*Reading distance depends on tag, antenna and environmental conditions

## Order Codes

Version	Order Code
RS232/RS485	R-IN-HF-5241HM
Ethernet	R-IN-HF-5242HM
Profibus	R-IN-HF-5243HM

iDTRONIC GmbH  
Ludwig-Reichling-Straße 4  
67059 Ludwigshafen  
GERMANY

Phone +49 (0) 621 66 90 09 4-0  
Fax +49 (0) 621 66 90 09 4-9  
E-Mail: [info@idtronic-rfid.com](mailto:info@idtronic-rfid.com)  
Web: [idtronic-rfid.com](http://idtronic-rfid.com)

For further information & prices, please contact [info@idtronic-rfid.com](mailto:info@idtronic-rfid.com)

Subject to alteration without prior notice  
©2020 iDTRONIC GmbH