

# Access Reader

### **PRODUCT DESCRIPTION**

The ID IDENT 2000 access reader combines QR/barcode and RFID technology into one device and impresses with fast reading speed, high recognition rate, and excellent compatibility.

Due to its low installation depth, it is well-suited for challenging installation situations. Depending on the application, the reader is available as a USB-HID variant. It reads RFID transponders such as cards, key fobs, or wristbands. It also reads all common 1D/2D barcodes in printed form or directly from a smartphone display.

With the accompanying "Config-Tool," the reader can be extensively configured and customized to meet specific requirements.

The ID IDENT 2000 can be integrated into turnstiles of the series:

- ID GATE 6200 Turnstile
- ID GATE 7700 Turnstile
- ID GATE 9200 Turnstile



#### **APPLICATIONS**

- Access control
- Gym
- · Baths / Spas
- · Companies & Institutions
- · Cultural institutions,
  - e.g. museums

#### **FEATURES**

- RFID and barcode reader in one
- Can be used in combination
  with our turnstiles
- · Acoustic and visual feedback
- Extensive configuration options
- Reads RFID transponders (e.g. cards, keyfobs or wristbands)

Phone:+49 (0)621 66 900 94-0 Mail: info@idtronic-group.com Web: idtronic-group.com



## **TECHNICAL DATA**

| ELECTRICAL SPECIFICATIONS |   | MECHANICAL SPECIFICATIONS       |  |
|---------------------------|---|---------------------------------|--|
| Power Supply              | 5 to 24 volts (broad voltage range)   | Dimensions                      | 88.3 x 88.3 x 28.35mm                    |
| Power Consumption         | 280 mA  | Material                        | PC + ABS                                 |
| Reading Speed             | 100 ms  |                                 |  |
| Reading Range             | 0 mm ~ 62.4 mm (QRCODE 15 mil)  | ENVIRONMENTAL CONDITIONS        |  |
| Barcode Type              | <b>2D:</b><br>QR Code,<br>DataMatrix,   | Temperature                     | -20°C up to 70°C                         |
|                           |   | Humidity                        | 5% up to 95%                             |
|                           | PDF417  |                                 |  |
|                           | <b>1D:</b><br>EAN-8/ -13,<br>UPC-A/ -E,<br>ISSN,  | SDK INFORMATION                 |  |
|                           |   | Supported OS                    | Windows (XP/7/8/10/11),<br>Linux, Mac    |
|                           | ISBN,   |                                 |  |
|                           | Codebar,<br>Code 39/ 128,<br>Interleaved 2 of 5,<br>Industrial 2 of 5,<br>Standard 2 of 5   | SUPPORTED STANDARDS / TAGS      |  |
|                           |   | RFID HF   NFC: 13.56 MHz        |  |
|                           |   |                                 | MIFARE Classic 1k,<br>MIFARE Classic 4k. |
| Light Source              | LED (white)   | RFID Options MIFARE Ultralight, |  |
| Image Sensor              | 640 x 480 CMOS  |                                 | Fudan                                    |
| Scan Function             | Automatic   |                                 |  |
| Interface                 | USB-HID mode development, serial<br>communication development,<br>(C/C++, C#, Java, DELPHI) |                                 |  |

## ORDER CODES

| VERSIONS                                   | ORDER CODES       |
|--|-------------------|
| ID IDENT 2000 - RFID / QR / Barcode reader | R-EA-ID2000-QR-HF |

## **PRODUCT IMAGES**



iDTRONIC GmbH Ludwig-Reichling-Straße 4 67059 Ludwigshafen GERMANY





Phone:+49 (0)621 66 900 94-0 Mail: info@idtronic-group.com Web: idtronic-group.com

Subject to change without notice. ©2024 iDTRONIC GmbH